

CAREY LIFT تحافظ على حزم المواسير ذات التكلفة العالية وتوفر الوقت و العمالة في مجالات التكرير و التصنيع و النقل و التشغيل و الصيانة.



كما تمكن CAREY LIFT عامل واحد من تحميل و إضاع عشرة أطنان من حزم المواسير في أقل من خمسة دقائق .

أضغط هنا  
لعرض الفيديو  
والمنشورات  
المجانية



CareyLifts are available in 6 models. The chart below will help you choose the CareyLift that is right for you.

Specifications	Model 40	Model 45	Model 60	Model 60-55	Model 65	Model 72.5
Maximum Bundle O.D.	40 inches	45 inches	60 inches	60 inches	65 inches	72.5
Maximum Lift	20,000 lbs	20,000 lbs	30,000 lbs	30,000 lbs	50,000 lbs	51,266 lbs
Max. Lift (without shock load)	30,000 lbs	30,000 lbs	50,000 lbs	55,000	65,000 lbs	68,355 lbs
Unit Weight	2,500 lbs	2,700 lbs	6,000 lbs	6,000 lbs	7,500 lbs	9,000 lbs
Overall Length	108 inches	108 inches	144 inches	144 inches	144 inches	144 Inches
Studs are Grade 8	Yes	Yes	Yes	Yes	Yes	Yes
"J" Arms are A514 GR-H T1	Yes	Yes	Yes	Yes	Yes	Yes
Plate is A36	Yes	Yes	Yes	Yes	Yes	Yes

CAREYLIFTS MEET OR EXCEED ASME B30.20 1993 STANDARDS

AND ARE "CE" CERTIFIED FOR EUROPE.

THE CAREYLIFT MEETS OR EXCEEDS AUSTRALIA STANDARDS AS-4991-2004

CareyLifts are made in the USA

Material Certificates are available upon request.

Certification documents are supplied with each unit purchase.